Printing date 28.03.2018 Version: 4 Revision: 28.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MAXI 99
- · Article number: 97380001
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Coating material
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RR

United Kingdom

Tel: +44 (0)151 422 1000 Fax: +44 (0)151 422 1011 @: info@zep.co.uk

web: www.zep.co.uk

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117 Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: sales@zepbenelux.com

ZEP ITALIA SRL

Via Netunese Km. 25.000 04011 Aprilia (LT) - Italy

Tel: +39.06.926691

Fax: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

· Further information obtainable from:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· 1.4 Emergency telephone number:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 28.03.2018 Revision: 28.03.2018 Version: 4

Trade name: MAXI 99

· Hazard pictograms

(Contd. of page 1)







· Signal word Danger

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy toluene

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	75-100%
EINECS: 265-150-3	Asp. Tox. 1, H304 STOT SE 3, H336	
CAS: 108-88-3	toluene	1-2.5%
EINECS: 203-625-9	♦ Flam. Liq. 2, H225	
Reg.nr.: 01-2119471310-51-xxxx	♠ Repr. 2, Ĥ361d; STOT RE 2, H373; Asp. Tox. 1, H304	
	\$\sqrt{5} \Skin Irrit. 2, H315; \STOT \SE 3, H336	

[•] Ingredients according to Detergents Regulation 648/2004/EC For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 28.03.2018 Version: 4 Revision: 28.03.2018

Trade name: MAXI 99

(Contd. of page 2)

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:			
108-88-3 toluene (1-2.5%)	108-88-3 toluene (1-2.5%)		
WEL (Great Britain)	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk		
127-18-4 tetrachloroethylene (<-0.1%)			
WEL (Great Britain)	Short-term value: 689 mg/m³, 100 ppm Long-term value: 345 mg/m³, 50 ppm		
IOELV (European Union)	Short-term value: 275 mg/m³, 40 ppm Long-term value: 138 mg/m³, 20 ppm Skin		

· DNELs

64742-48-9 Naphtha (petroleum), hydrotreated heavy

0.7.12 .0	or, 12 to 5 trapiana (penoteum), nyaron euron		
Oral	DNEL Long term-systemic	300 mg/kg human/day (consumer)	
Dermal	DNEL Long term-systemic	300 mg/kg human/day (consumer)	
		300 mg/kg human/day (worker)	
Inhalativ	DNEL Long term-systemic mg/m3	900 mg/m3 (consumer)	
		1,500 mg/m3 (worker)	

Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 28.03.2018 Version: 4 Revision: 28.03.2018

Trade name: MAXI 99

(Contd. of page 3)

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter AX

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

PVA gloves

- · Not suitable are gloves made of the following materials: Strong material gloves
- · Eye protection:



Tightly sealed goggles

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: Undetermined.

· Flash point: 40 °C

· Flammability (solid, gas): Not applicable.

• Ignition temperature: 240 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7 Vol %

· Vapour pressure at 20 °C: 42 hPa

• **Density at 20 °C:** 0.8 g/cm³

• Relative density Not determined.
• Vapour density Not determined.

• Evaporation rate Not determined.

(Contd. on page 5)

Printing date 28.03.2018 Version: 4 Revision: 28.03.2018

Trade name: MAXI 99

	(Contd. of p	age
Solubility in / Miscibility with water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	96,0 %	
Swiss VOC:	92.04 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

Acute toxicity Bused on available data, the classification of the hat are not met.			
· LD/LC50 values relevant for classification:			
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>5,000 mg/kg (rab)	
Inhalative	LC50 / 4 h	4,951 mg/ltr (Rat)	
108-88-3 to	108-88-3 toluene		
Oral	LD50	5,000 mg/kg (Rat)	
Dermal	LD50	12,124 mg/kg (rab)	
Inhalative	LC50 / 4 h	5,320 mg/ltr (Mouse)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)

Printing date 28.03.2018 Version: 4 Revision: 28.03.2018

Trade name: MAXI 99

(Contd. of page 5)

- Danger to drinking water if even small quantities leak into the ground.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations
- · Uncleaned packaging:
- · Recommendation: Disposal in accordance with administrative provisions

1.4.1 TINI NI1	
14.1 UN-Number ADR, IMDG, IATA	UN3295
14.2 UN proper shipping name	
ADR	3295 HYDROCARBONS, LIQUID, N.O.S.
IMDG, IATA	HYDROCARBONS, LIQUID, N.O.S.
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3 1 turmuote riquitus.
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number: Stowage Category	F-E,S-D A
14.7 Transport in bulk according to Annex II	
the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	D/E

Printing date 28.03.2018 Version: 4 Revision: 28.03.2018

Trade name: MAXI 99

(Contd. of page 6)

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E3

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml

UN "Model Regulation":

UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 1907/2006 - Reach;

Reg. (EC) n. 2015/830 annex II of REACH;

Reg. (EC) n. 648/04 (Detergents);

Reg. (EC) n. 528/12 (Biocides BPR);

Reg. (EC) n. 1223/2009 (Cosmetics);

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40, 48
- · National regulations:
- Technical instructions (air):

Class	Share in %
NK	75-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Department issuing SDS:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Contact:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 8)

Page 8/8

Safety data sheet According to 1907/2006/EC, Article 31 REACH

Printing date 28.03.2018 Revision: 28.03.2018 Version: 4

Trade name: MAXI 99

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

VIVIS: Very Persistent and Very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 2: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

(Contd. of page 7)