



Product Specification Report

1.0/99240001/0918

Multipurpose lubricant with high penetrating power. The product is colourless, and based on a mix of penetrating oils, solvents and additives. A 5 in 1 product: anti-seize, lubricant, deoxidizer, protective agent and cleaner.

ZEP 5U AERO

5 in 1 anti-seize spray

FEATURES:

Anti-seize and deoxidizer	The spray penetrates quickly between metal parts, even if oxidised or rusted, loosening seized components
Cleaning action	Thanks to the high penetrating power, the oil also penetrates deposits of grease or other dirt so they are easier to clean
Protective and water repellent	ZEP 5 U AERO leaves a light, protective film on the part it's sprayed on, protecting metal parts against rust, water and damp
Safe	Chlorinated-solvent-free, it does not damage paint or metal parts

APPLICATIONS:

ZEP 5 U AERO has been specifically formulated to be used on seized and rusted parts such as screws, bolts, chains, mechanical components and all mechanical parts that need lubricating. Ideal for the industrial, mechanical, car and transport sectors and in general in all sectors where mechanical maintenance is done.

SPECIFICATIONS:

Form Aerosol
Colour Colourless
Odour Characteristic
Solubility Insoluble
Net volume 400 ml
Gross volume 500 ml

ACTIVE INGREDIENTS:

- Penetrating oil mix
- Selected solvents
- Additives

INSTRUCTIONS FOR USE:

Shake the can well before using. Spray a sufficient amount of the product on the parts to be lubricated from a distance of around 20 - 25 cm. The nozzle of the aerosol helps direct the product making the spray easy to apply where needed. On tightly seized parts, let it penetrate for up to 5 minutes. If necessary tap the parts lightly with a hammer to help ZEP 5U AERO penetrate. Disassemble the component by applying force gradually. Use ZEP 5U AERO at ambient temperature for best results.

PRECAUTIONS FOR USE:

Store at 8 - 28°C. Outside this temperature range the product's performance may be affected. Refer to the Safety Data Sheet for more information.

COMPATIBILITY:

For all metals. Does not damage paint.

ISO 9001

BUREAU VERITAS
Certification



N° 206982

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.

IT

Zep Italia s.r.l.
T • 800 016 918

Numero Verde Tecnico
800-579185
tecnico@zepeurope.com
www.zep.it

UK

Zep UK Ltd.
T • 0151 422 1000
F • 0151 422 1011
info@zep.co.uk
www.zep.co.uk

BE

Zep Industries BV
T • 02 347 01 17
F • 02 347 13 95
sales@zep.be
www.zepindustries.be

NL

Zep Industries BV
T • 0164 250100
F • 0164 266710
info@zepbenelux.com
www.zepindustries.nl

DE

Zep Industries BV
T • 0521 174158
F • 0521 5217114
sales@zepbenelux.com
www.zepindustries.de