



Product Specification Report

V. 1.0

RESTORE AERO NEW is a mixture of acrylic resins and plasticizers added to a fast evaporating solvent. Packaged in spray can for quick application.

RESTORE AERO NEW

Fast evaporating acrylic-based protection

FEATURES:

Protective action	It seals metal surfaces and paintwork to protect them.
Excellent finish	The product dries quickly leaving an acrylic coating that has a clear, glossy finish. Non-yellowing, non-oily and non-combustible.
Practical	Quick and easy to apply thanks to the ready to use spray can packaging.
Safe	Does not contain CFCs, trichloroethane or chlorinated solvents.

APPLICATIONS:

Ideal for coating mechanical parts, motors, electrical cables with a shiny and protective surface and to seal and protect all surfaces exposed to the weather. Ideal for the automotive sector, electric companies, auto repair shops, industrial sector in general.

SPECIFICATIONS:

Chemical and physical properties	Value
Form	Spray can
Colour	Transparent
Odour	Cherry
Specific weight (20 ° C)	0.88 g/cm ³
Miscibility in water	Not soluble
VOC (%)	82%
Gross volume	800 ml
Net volume	600 ml

COMPATIBILITY:

Plastics and metals in general

INSTRUCTIONS:

Remove all traces of dirt and grease from surfaces to be treated. Allow the surface to dry with no trace of detergent or solvent.

- Hold the can 25 cm from the point of application
- Spray with horizontal movement from the top downwards
- We recommend applying two light layers instead of one thick one
- Allow to dry for at least 10 minutes
- After applying, turn the can upside down to clean the valve

The product can be easily removed with a ZEP line solvent.

SAFETY PRECAUTIONS:

For best results we recommend applying RESTORE AERO NEW at room temperature. It may damage some types of plastics, we recommend a preliminary compatibility test before application over the entire surface. For further information, please refer to the safety data sheet.

All the information in this document is based on our practical experience and/or laboratory tests. Because of the wide spectrum of conditions for the use and unpredictable human factors, you should always test our products before final use. This technical data sheet may already have been revised pursuant to current legislation, the availability of individual ingredients or newly acquired information. We are able to send, upon request, the latest applicable version, which is at the same time the most up-to-date version.