Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)
- · Article number: 24600001
- · UFI: VTNO-7VSN-J82C-OTTE
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages PW Widespread use by professional workers
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ZEP ITALIA SRL

Piazzale Luigi Cadorna, 2

20123 Milano (MI) - Italy;

Via Nettunense Km. 25.000

04011 Aprilia (LT) - Italy

T: +39.06.926691

F: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: info@zepbenelux.com

Distributed in the UK by:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RD

United Kingdom

Tel: +44 (0)151 422 1000

Fax: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

Further information obtainable from:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

1.4 Emergency telephone number:

NHS +44 0845 46 47 (England or Wales); +44 08454 24 24 24 (Scotland)

emergency number (europe): 112

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





GHS02 GHS0

- · Signal word Danger
- · Hazard-determining components of labelling:

pentane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:	· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane	❖ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%
CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30-xxxx	pentane	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 	≥10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane	❖ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	and isobutane	<page-header> Flam. Gas 1A, H220 Press. Gas (Comp.), H280</page-header>	5-10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Seek immediate medical advice.

(Contd. on page 3)

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 2)

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Mount respiratory protective device.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Absorb liquid components with liquid-binding material.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 109-66-0 pentane

IOELV Long-term value: 3000 mg/m³, 1000 ppm

(Contd. on page 4)

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter A/P2

Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Not suitable are gloves made of the following materials: Strong material gloves
- · Eye protection:



Safety glasses

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information

· Appearance:

Form: Aerosol
Colour: White
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: -44 °C

• Flash point: -97 °C

• Flammability (solid, gas): Not applicable.

• Ignition temperature: 210 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

· Explosion limits:

 Lower:
 0.5 Vol %

 Upper:
 8.5 Vol %

· Vapour pressure at 20 °C: 2,100 hPa

• Density at 20 °C: 0.701 g/cm³

• Relative density Not determined.

(Contd. on page 5)

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

	(Cont	td. of pag
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	55.0 %	
EÜ-VOC:	378.5 g/l	
EU-VOC	54.00 %	
Swiss VOC:	54.00 %	
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values	relevant fo	r classification:

CAS: 109-66-0 pentane		
Oral	LD50	>16,000 mg/kg (Rat)
Dermal	LD50	>2,500 mg/kg (Rat)
		>5,000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	>100 mg/l (Rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 5)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 109-66-0 pentane

LC50 / 96 h 4.26 mg/ltr (Oncorhynchus mykiss (Rainbow trout))

EC 50 / 48 h 2.7 mg/ltr (Daphnia magna (water flea))

EC 50 / 72 H 10.7 (-)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes: Harmful to aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations

	1 8 33 8		
· Europ	· European waste catalogue		
15 00	00 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01	packaging (including separately collected municipal packaging waste)		
15 01	04 metallic packaging		
HP3	Flammable		
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
HP14	Ecotoxic		

- · Uncleaned packaging:
- · Recommendation: Disposal in accordance with administrative provisions

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · ADR 1950 AEROSOLS
 · IMDG AEROSOLS
- · IATA AEROSOLS, flammable
- · 14.3 Transport hazard class(es)
- \cdot ADR



· Class
 · Label
 2 5F Gases.
 2.1

(Contd. on page 7)

Printing date 31.05.2021 Revision: 31.05.2021 Version: 4

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

	(Contd. of pag
· IMDG, IATA	
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Code · Segregation Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 exceptor division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Mar the IBC Code	pol and Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 2015/830 annex II of REACH;

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





· Signal word Danger

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 7)

· Hazard-determining components of labelling:

pentane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- National regulations:
- · Technical instructions (air):

Class	Share in %
NK	54.0

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing SDS:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Contact:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

(Contd. on page 9)

Printing date 31.05.2021 Version: 4 Revision: 31.05.2021

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 8)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

WELL: The highest acceptable concentration

IOELV: Indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

(Contd. on page 10)

Printing date 31.05.2021 Revision: 31.05.2021 Version: 4

Trade name: SANITARY SPRAY LUBRICANT EU (Listed NSF H1: n 144023)

(Contd. of page 9)

Annex: Exposure scenario

- · Short title of the exposure scenario For the finished product.
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Aerosol
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity According to directions for use.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure Use only on hard ground.
- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure Keep out of the reach of children.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

- · Personal protective measures Protective gloves
- · Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

- Environmental protection measures
- · Water Do not allow to reach sewage system.
- · Soil Prevent contamination of soil.
- · Disposal measures

Disposal in accordance with administrative provisions

Ensure that waste is collected and contained.

- · Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.