Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SOLVENT
- · Article number: 97460001
- · UFI: T2T3-V0K8-500C-6FU9
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

IS Use at industrial Sites

PW Widespread use by professional workers

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Thinner, Diluent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ZEP ĪTALIA SRL

Piazzale Luigi Cadorna, 2

20123 Milano (MI) - Italy;

Via Nettunense Km. 25.000

04011 Aprilia (LT) - Italy

T: +39.06.926691

F: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: info@zepbenelux.com

Distributed in the UK by:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RD

United Kingdom

Tel: +44 (0)151 422 1000

Fax: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

#### · Further information obtainable from:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· 1.4 Emergency telephone number:

NHS +44 0845 46 47 (England or Wales); +44 08454 24 24 24 (Scotland)

emergency number (europe): 112

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Acute Tox. 4 H312 Harmful in contact with skin.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

(Contd. of page 1)

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways. Asp. Tox. 1 H304

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms









GHS08

GHS02

GHS05

GHS07

· Signal word Danger

#### · Hazard-determining components of labelling:

xylene butanol

Aromatic hydrocarbons, C8

reaction mass of ethylbenzene and m-xylene and p-xylene

Hazard statements

H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

- 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
	butanol Flam. Liq. 3, H226 Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335-H336	10-25%	
EINECS: 215-535-7 Index number: 601-022-00-9	xylene  Flam. Liq. 3, H226  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%	
CAS: 90989-38-1 EINECS: 292-694-9 Index number: 648-010-00-X	Aromatic hydrocarbons, C8 (Note J)  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%	
EINECS: 204-658-1	n-butyl acetate  Flam. Liq. 3, H226 STOT SE 3, H336	10-25%	
EC number: 905-562-9	reaction mass of ethylbenzene and m-xylene and p-xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%	

(Contd. on page 3)

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

(Contd. of page 2)

· Additional information:

Ingredients according to Detergents Regulation 648/2004/EC

Aliphatic hydrocarbons

≥15 - <30%

· Additional Information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

*In case of unconsciousness place patient stably in side position for transportation.* 

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binders).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Use only in well ventilated areas.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

(Contd. of page 3)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide solvent resistant, sealed floor.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

CAS: 123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Do not eat or drink while working.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

PVA gloves

· Not suitable are gloves made of the following materials: Strong material gloves

(Contd. on page 5)

(Contd. of page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

· Eye protection:



· **Body protection:** Solvent resistant protective clothing

# SECTION 9: Physical and chemical properties

9.1 Information on	hasic physical an	d chemical	nronerties
7.1 Inivimunon on	vasic viivsicai an	a cnemicai	vi ovei ues

General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

· Flash point: 25 °C

· Flammability (solid, gas): Not applicable.

• Ignition temperature: 425 °C

• Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Explosion limits:

 Lower:
 1.1 Vol %

 Upper:
 12 Vol %

· Vapour pressure at 20 °C: 42 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 0.825 g/cm³
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 100.0 %

 Swiss VOC:
 62.50 %

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

(Contd. of page 5)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin.

· LD/LC50	values relevan	t for classification:
ATE (Acu	te Toxicity Es	timates)
Dermal	LD50	1,760 mg/kg
Inhalative	LC50 / 4 h	44 mg/l
CAS: 78-8	3-1 butanol	
Oral	LD50	2,460 mg/kg (Rat)
Dermal	LD50	4,200 mg/kg (Rabbit)
CAS: 123-	86-4 n-butyl a	icetate
Oral	LD50	10,770 mg/kg (Rat)
Dermal	LD50	>17,600 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	>21 mg/l (Rat)
	LC50/ 24 h	205 mg/ltr (Daphnia magna (water flea))
	EC 50 / 96 h	320 mg/ltr (Selenastrum capricornutum (Algae))

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Carcinogenicity} \ \textit{Based on available data, the classification criteria are not met.}$
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations

(Contd. on page 7)

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

	(Contd. of page 6)
· Europe	ean waste catalogue
HP3 Fl	Flammable
HP4 Ir	rritant - skin irritation and eye damage
HP5 Sp	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6 Ac	Icute Toxicity

- · Uncleaned packaging: · Recommendation: Disposal in accordance with administrative provisions

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTANOL (ISOBUTYL ALCOHOL), BUTYL ACETATES)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ISOBUTANOL (ISOBUTYL ALCOHOL), BUTYL ACETATES)
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
MDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
4.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30 F-E,S-E
EMS Number: Stowage Category	7- <u>L,3-L</u> A
4.7 Transport in bulk according to Annex II of Mar	nol and
he IBC Code	Not applicable.
Fransport/Additional information:	
ADR	
Limited quantities (LQ)	<i>5L</i>
Excepted quantities ( $\overline{E} extbf{ ilde{Q}}$ )	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	Maximum nei quantity per outer packaging. 1000 mi 3
Tunnel restriction code	D/E
IMDG	
in D G	5L

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

	(Contd. of page
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTANOL (ISOBUTYL ALCOHOL), BUTYL ACETATES), 3, III

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 2015/830 annex II of REACH;

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

Reg (EC) n. 648/2004 - Detergents

- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms









GHS02

GHS05

GHS07

GHS08

- · Signal word Danger
- Hazard-determining components of labelling:

xylene

butanol

Aromatic hydrocarbons, C8

reaction mass of ethylbenzene and m-xylene and p-xylene

· Hazard statements

H226 Flammable liquid and vapour. H312 Harmful in contact with skin.

H315 Causes skin irritation.
H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

### · Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 9)

Printing date 18.05.2021 Version: 4 Revision: 18.05.2021

Trade name: SOLVENT

(Contd. of page 8)

- National regulations:
- · Technical instructions (air):

Class	Share in	%
NK	62.5	

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008 Calculation method

#### Department issuing SDS:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

#### Contact:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

WELL: The highest acceptable concentration IOELV: Indicative occupational exposure limit values Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category I

\* Data compared to the previous version altered.